

# Operations Bulletin

**JIG**  
jigonline.com

---

Bulletin 90

Hinged Hydrant Pit Lids

May 2016


---

## Introduction

JIG Standards (JIG 2 section 3.5.4) require that all hydrant pit covers shall be tethered or permanently connected to pits. One way of meeting this requirement is to have a hinged lid that is permanently connected to the pit. There are various designs of hinged lids available from a number of manufacturers – when open, some lay flat on the ground and others repose in a vertical or near vertical position.

A number of stakeholders have raised concerns that non-lay-flat hinged hydrant pit lids may interfere with the breakaway characteristics of EI 1584 Third Edition Hydrant Pit Couplers. The concern is that if the lid is contacted by a moving apron service vehicle then it could trap the hydrant pit coupler in a clamshell type action preventing it from breaking away cleanly as it is designed to do – continued pressure on the lid could result in a partial breakaway or pit coupler casing fracture and the potential risk of a pressurised release of fuel from the hydrant. The effect this would have on the hydrant riser pipe is not known.

The Energy Institute, who published EI 1584 Third Edition, carried out a study of this scenario which involved modelling and also some destructive testing using a specially designed test rig and two commonly used pit couplers from different manufacturers. In this particular test scenario the presence of the lid prevented both models of pit coupler from breaking away as designed. When the lid was removed the two models of pit coupler both broke away as intended.



The static load testing carried out so far demonstrates that the presence of the non-lay-flat hinged pit lid may prevent the pit coupler from breaking away as intended.

All three current manufacturers of EI 1584 Third Edition hydrant pit couplers have recommended that their equipment is not used in conjunction with non-lay-flat hinged pit lids.

# Operations Bulletin



Bulletin 90

Hinged Hydrant Pit Lids

May 2016

## Action

It is clear that the presence of the non-lay-flat lid generates a downward force on the hydrant pit coupler that does not arise with a lay-flat lid. In the absence of further testing, including stress measurement, Hydrant Operators shall specify the lay-flat type for any new purchases of hinged hydrant pit lids.

Manufacturers of non-lay-flat hinged hydrant pit lids may be able to propose a modification to the lid arrangement. Hydrant Operators shall either change existing non-lay-flat hinged hydrant pit lids to lay-flat lids or modify existing non-lay-flat hinged hydrant pit lids as recommended by the manufacturers, as soon as practical and no later than the end of December 2018. Modified lids shall continue to meet the JIG requirement of either being permanently connected or tethered to the pit. To achieve this requirement, it is recommended that equipment suppliers be contacted as soon as possible.

## Actions to Implement this Bulletin (See Table 1 for Action Type Codes)

Action Description	Action Type	Target Completion Date
Hydrant Operators to ensure that non-lay-flat hinged pit lids are modified or replaced	JS	31st Dec 2018

Table 1 Action Type Codes

Action Types	JIG Bulletin Action Type Definition
JS	Change to JIG Standard – to be adopted by JV and/or Operator to continue to meet the JIG Standard(s) (JIG 1, 2, 4) (**).
RP	JIG Recommended Practice which the JV should consider adopting as its own practice (**).
I	Issued for information purposes only.
Note (**) - If the JV agreements require any of the JIG Standards and/or any of the JIG Common Processes as the governing operational standard then adoption of changes to applicable JIG Standards and/or Common Processes should not be considered optional by the JV Board.	

*Note:* This document is intended for the guidance of Members of JIG and companies affiliated with Members of JIG, and does not preclude the use of any other operating procedures, equipment or inspection procedures.


The information contained in this publication is subject to constant review in the light of changing government requirements and regulations. Although efforts are made to keep this information up-to-date, accurate, complete, and free from error, we make no representation, warranty or guarantee, whether express or implied, that the information is up-to-date, accurate, complete, free from error, or in compliance with applicable law and regulations. No subscriber or other reader should act on the basis of any such information without referring to applicable laws and regulations and/or without taking appropriate professional advice. None of JIG, its Members, the Companies affiliated with its Members accepts responsibility for any loss or damage, whether in contract, tort (including negligence), breach of statutory duty, or otherwise, even if foreseeable, arising under or in connection with your use, adoption or reliance on the information in this document. You use this information at your own risk, but for the full terms and conditions concerning use of this document, please refer to <http://www.jigonline.com/legal-and-copyright/>

JIG is the owner of the copyright and all intellectual property rights in the publication. IATA uses such rights with permission from JIG.


Endorsed by IATA






Technical Fuel Group






DETAIL C  
SCALE 1 : 1



SECTION A-A



PROJECT NO. K1-149-DWG-001		DATE 11/11/11	
PROJECT NAME JET A1 PIT LID		DRAWN BY [REDACTED]	
PROJECT LOCATION [REDACTED]		CHECKED BY [REDACTED]	
PROJECT NO. K1-149-DWG-001		DATE 11/11/11	
PROJECT NAME JET A1 PIT LID		DRAWN BY [REDACTED]	
PROJECT LOCATION [REDACTED]		CHECKED BY [REDACTED]	
PROJECT NO. K1-149-DWG-001		DATE 11/11/11	
PROJECT NAME JET A1 PIT LID		DRAWN BY [REDACTED]	
PROJECT LOCATION [REDACTED]		CHECKED BY [REDACTED]	



UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS DIMENSIONS IN PARENTHESES ARE IN INCHES		FINISH: ANODIZED OXIDE COATING AS PER TECHNICAL SPECIFICATION K149-16P-001		DENURE AND REBARK SHARP EDGES		DO NOT SCALE DRAWING		REVISION	
POLYMER: LINEAR: 0.5MM DIAMETER: 0.3MM									
NAME	SIGNATURE	DATE	TITLE						
DRW	IS	15.03.17	PIT LID TYPE B						
CHKD	TRM	15.03.17							
APPVD	TRM	15.03.17							
MFC									
QA			MATERIAL: CAST ALUMINUM ALLOY						
			SPECIFIC: 16. EG						
DWG NO			KI-T49-DWG-002			A3			SHEET 01/1

